

TM-2000 TM-3000

Flat LCD Touch Monitors



TM-2000 / TM-3000 Touch Monitors

With a small footprint, the TM series of touch monitors are especially attractive and space efficient in POS applications. The large bright displays are adjustable for clear viewing in high or low light environments and the TM series touch interface increases accuracy and improves operator efficiency. All include a heavy-duty metal base and standard wall mount option. Cables and connectors are easy to access, yet safe and secure from interference.



Flip Down Door Protects Liquid Resistant Control Panel



Optional MSR



Tiltable LCD Display



Standard VESA Mounting Bracket Accepted

SPECIFICATIONS

	TM-2000	TM-3000
Display Type:	Active Matrix TFT LCD	Active Matrix TFT LCD
LCD Size:	15.1"	17.0"
Display Area:	12" x 9" 304mm x 228mm	13.52" x 10.8" 343mm x 276mm
Monitor Dimensions:	15.3"W x 13.8"H x 9.8"D 393 W x 355 H x 250 D (mm)	17.28"W x 16.24"H x 9.8"D 440 W x 413 H x 250 D (mm)
Highest Resolution:	1024 x 768	1280 x 1024
Colors:	16.7 Million	16.7 Million
Brightness:	250 cd/m ²	250 cd/m ²
Contrast Ratio:	350 : 1	400 : 1
Adjustable Angle:	70° to 240°	70° to 240°
Viewing Angle:	H = 150° V = 140°	H = 160° V = 135°
Input Signal:	RGB Analog	RGB Analog
Input Connector:	D-Sub 15 Pin Female	D-Sub 15 Pin Female
Power Supply:	2.5A 12V External Adapter	2.5A 12V External Adapter
Power Consumption:	.15 Amp / 18V Maximum	.15 Amp / 18V Maximum
Operating Temperature:	32° to 114°F (0° to 40°C)	32° to 114°F (0° to 40°C)
Humidity (Non-Cond.):	10% to 90%	10% to 90%
Touch Panel –	ELO: ELO 5-Wire Resistive LIYI: LIYI 4-Wire Resistive	ELO 5-Wire Resistive LIYI 4-Wire Resistive
Optional MSR:	Tracks 1, 2 and 3	Tracks 1, 2 and 3
MSR Interface:	PS/2 K/B	PS/2 K/B
Wall Mount Bracket:	Standard	Standard
Cabinet Color:	Choice of Ivory or Black	Choice of Ivory or Black
Warranty:	2 Year	2 Year



Cover Photo
TM-2000 shown with optional MSR.