

# Signature

## TM-2016



### Features



## Specification

TSM-15	
Size	15" Diagonal TFT Active Matrix Panel
Maximum Resolution	1024 X 768
Contrast Ratio	600:1
Brightness (Backlight Type)	250 nits (No Touch), 225 nits (Projected Capacitive)
View Angle	H:170°, V:160°
Touch LCD Display	
Touch Screen	Projected Capacitive
Stack Up	Glass on Glass
Touch Points	10
Optional Coating	AG Coating
IO ports	
Serial Port	NA
USB Port	1 x USB HID (Type B)
Video Port	1 x VGA (DB15), 1 x DVI-D
Audio Port	NA
DC Input	1 x 2.0 mm DC Jack
Physical Properties	
Power Supply	50W (12V / 4.16A) External Power Adaptor
Speaker	NA
Housing Color	Black
Construction	Glass, SECC Metal
Compliance	IP65 Compliant Front Side, IPX1
Dimensions (W x H x D) mm	337.4 x 304.2 x 200.9 mm (With Stand), 337.4 x 265.4 x 44.3 mm (Without Stand)
Net Weight (kg)	4.3 kg (With Stand)
Gross Weight (kg)	6.1 kg (With Stand)
Carton (mm)	415 x 370 x 290 mm
VESA	100 x 100 mm
Safety	
Certifications	CE, UL, CUL, FCC-B, CCC, RoHS
Environment	
Operating Temperature	0°C ~ 40°C, 20% ~ 80% RH, Non-Condensing
Storage Temperatures	-20°C ~ 60°C, 10% ~ 90% RH, Non-Condensing